

# Gripsure Cumaru

## TECHNICAL SPECIFICATION



### Slip resistance

Gripsure Cumaru decking profile using two inserts achieves an average PTV value of 85 (pendulum test value). Gripsure non-slip decking has been independently tested using the pendulum test (the operation and calibration of which are described in BS7976:2002 parts 1 and 3) operated to the United Kingdom Slip Resistance Group (UKSRG) and comes with a 15-year performance warranty.

---

### Aggregate inserts

Gripsure Cumaru decking uses a 0.5mm - 1.4mm double washed and screened Guyanan Calcined Bauxite – grey colour with a minimum PSV (polished stone value) of 70.

---

### Timber board

Gripsure Cumaru is made using naturally durable Cumaru hardwood timber. Cumaru is classified within BS EN 350-2 as Class 1 - Very Durable. With a 25+ year expected in-service life, Gripsure Cumaru is ideal for any application where durability is required.

Gripsure Cumaru can be supplied with FSC® certification – Certificate No TT-COC-003864.

Gripsure Cumaru board profile dimensions are 21mm depth x 145mm width. The lengths available are 2m - 4.5m. A bespoke cutting service is available for any lengths.

---

### Maintenance

Gripsure Cumaru is a low maintenance product, no further preservative treatment is necessary. The timber will naturally weather and fade over time to a lighter sun bleached silvery grey finish.

Gripsure Cumaru can be stained or painted. Decking oil can be applied every 12 months to give extra protection to the timber.

Gripsure Cumaru is pressure washable – it is recommended to remove dirt and mould build up across the surface of the board and inserts every 12 months, using a 150bar water pressure washer with fan nozzle at minimum distance of 150mm.

---

### Cross cut components

Any cuts, notches or drill holes to Gripsure Cumaru decking do not require any treatment. Gripsure recommend using a Stehle polycrystalline diamond disk blade to cut through the hardwood timber and non-slip strips.

Gripsure recommends pre-drilling hardwood decking boards and using Spax stainless steel decking screws to fix boards in place.

Contact us for more information

01726 844616 | [info@gripsure.co.uk](mailto:info@gripsure.co.uk) | [www.gripsure.co.uk](http://www.gripsure.co.uk)  
Unit D2(23) Rockhill Business Park, Higher Bugle, Cornwall, PL26 8RA