

Gripsure Yellow Balau

TECHNICAL SPECIFICATION



Slip resistance

Gripsure Balau decking profile using two inserts achieves an average PTV value of 85 (pendulum test value). Gripsure non-slip decking has been independently tested using the pendulum test (the operation and calibration of which are described in BS7976:2002 parts 1 and 3) operated to the United Kingdom Slip Resistance Group (UKSRG) and comes with a 15-year performance warranty.

Aggregate inserts

Gripsure Balau decking uses a 0.5mm - 1.4mm double washed and screened Guyanan Calcined Bauxite – grey colour with a minimum PSV (polished stone value) of 70.

Timber board

Gripsure Balau is made using Balau hardwood, an extremely high-quality timber, ideal for situations where style and appearance are paramount. Extremely strong and hard-wearing, and with an exceptional 50+ year expected in-service life, Gripsure Balau is ideal for any application. Available as a smooth or grooved profile.

Gripsure Balau can be supplied with FSC® certification – Certificate No TT-COC-003864.

Gripsure Balau's board profile dimensions are 21mm depth x 145mm width or 29mm x 145mm. The lengths available are 2m - 4.5m. A bespoke cutting service is available for any lengths.

Maintenance

Gripsure Balau is a low maintenance product, no further preservative treatment is necessary. The timber will naturally weather and fade over time to a lighter sun bleached silvery grey finish.

Gripsure Balau can be stained or painted. Decking oil can be applied every 12 months to give extra protection to the timber.

Gripsure Balau is pressure washable – it is recommended to remove dirt and mould build up across the surface of the board and inserts every 12 months, using a 150bar water pressure washer with fan nozzle at minimum distance of 150mm.

Cross cut components

Any cuts, notches or drill holes to Gripsure Balau decking do not require any treatment. Gripsure recommend using a Stehle polycrystalline diamond disk blade to cut through the hardwood timber and non-slip strips.

Gripsure recommends pre-drilling hardwood decking boards and using Spax stainless steel decking screws to fix boards in place.

Contact us for more information

01726 844616 | info@gripsure.co.uk | www.gripsure.co.uk
Unit D2(23) Rockhill Business Park, Higher Bugle, Cornwall, PL26 8RA