

# ReRoot Barrier Ribbed



## Overview

ReRoot 300, ReRoot 600 and ReRoot 1000 products are ribbed root barriers designed for the protection of paved surfaces, shallow service ducts and utilities.

This versatile root management system can be used to surround individual or groups of trees because the ribs are proven to divert lateral root growth downwards which has many benefits.

## Features

- Available in 300mm, 600mm and 1000mm depths
- Supplied in roll form and cut to order in 10m increments to minimise waste
- Recycled HDPE is resistant to puncture, biodegradation, and photodegradation
- ReRoot jointing tape allows root-proof joints

## Benefits

- Prevents 'root girdling' – a fatal rooting pattern
- Deeper root growth improves drought tolerance and tree stability
- Guides roots away from areas vulnerable to de-icing salts
- Prevents pavement 'root heave' effectively eliminating trip hazards
- Ease of installation in virtually all situations with no specialist equipment required



## Technical Specification

Code	Type	Depth	Thickness	Length (roll size)	Material	Finish	Colour
RER300A	Ribbed	300mm	1mm	30m	HDPE	Natural	Black
RER600A	Ribbed	600mm	1mm	30m	HDPE	Natural	Black
RER1000A	Ribbed	1000mm	1mm	30m	HDPE	Natural	Black



## Material Characteristics

Properties	ISO	Value
<b>Mechanical</b>		
Izod Impact, notched	kJ/m <sup>2</sup>	>13 >10
Stress at yield	MPa	23-26
Stress at break	MPa	28-30
Strain at break	%	>600
Flexular Modulus	MPa	950-1000
Shore D hardness		60-63
<b>Physical</b>		
Density	g/cc	0.97
	2%	2.5 - 3.0
	g/10min	<0.8
<b>Thermal</b>		
VST@10N (VST/A)	%	115- 130
HDT@0.45mPa (HDT/B)	°C	73- 80



## Storage

Not applicable



## Maintenance

Not applicable