

# CLD LockMaster S4

Swing Gate System to LPS 1175 D10 (SR4)/E3/G1 Issue 8



Find out more  
Scan for more information

## Description

CLD LockMaster S4 swing gates have been specially developed to blend in seamlessly with a CLD Securus fence line. Available using a Securus S4 infill panel, LockMaster S4 offers security rated access control, whilst maintaining aesthetics. Rigorously tested by the Loss Prevention Certification Board (LPCB) to guarantee a minimum delay of 10 minutes against attack, LockMaster S4 is also Secured by Design accredited, making it a police preferred specification for security.

## Features

Ideal for High Security sites, Nuclear, CNI sites, Prisons, MoD and government, Data centres, Utilities, Police stations

Double or single leaf opening

Heavy duty hinges



Exploded view of post and fixing details for the CLD LockMaster S4  
This product has additional features not demonstrated for security reasons



[cld-systems.com](http://cld-systems.com)

# CLD LockMaster S4

Swing Gate System to LPS 1175 D10 (SR4)/E3/G1 Issue 8

## Product Technical Information

Standard	LPS 1175 D10 (SR4) Issue 8 BS1722-14: 2017 BS EN ISO 1461:2009 BS EN 13438:2013 Secured by Design - Police Preferred Specification
Description	Open mesh steel high security gate system with mesh infill, to match fencing
Infill Panel Options	Securus S4
Panel Width	To suit mesh infill panels: Single leaf: 900mm minimum to 2500mm maximum Double leaf: 1200mm to 8000mm maximum
Available Heights	2800mm to 5000mm to match fence panel, Single leaf gates always have lintel panel
Nominal Heights	2.8m to 5m
Finish	Polyester powder-coated to 60-80 microns or 160-200 microns with marine grade and metallics. Any RAL colour available
Gate Frame	To suit mesh infill panels: Vertical stiles: minimum of 100mm x 50mm x 3mm rectangular hollow section Horizontal rails: minimum of 100mm x 50mm x 3mm rectangular hollow section Galvanised and powder-coated to match fencing
Topping options	Required: Saw tooth topping, Barbed wire, razor wire, cranked or straight.
Configuration	Double leaf/ single leaf / opening inwards or outwards as required
Locking	Slide bar with certified padlock
Hinges	3 x Superhinge SH30
Post dimensions	150mm x 150mm min
Foundations	Posts baseplated and fixed with M20 min anchors in suitable concrete foundation 100mm below finish ground level. Note: Contractor/ client is responsible for the foundation size suitable for the ground conditions
Warranty	Gate: Minimum of 15 years against manufacturing defects. Auto-element: Minimum of 12 months.
Notes	All dimensions are nominal, for further information please contact CLD Fencing Systems. Information is correct at time of production. As part of our policy of continuous improvement, we reserve the right to alter product specification without notice.

## System Details

## Disclaimer

Fencing should be installed in accordance with BS 1722-14. Every care has been taken to ensure that all information provided on this data sheet is accurate. CLD Fencing Systems Ltd reserves the right to change product specification at any time. Please ensure that you have the latest information which can be found on our website or by contacting our team.

Document Reference - CLD\_LockMaster\_S4\_DS\_20230504