

Palisade

Description

Barkers' palisade is a hugely popular, versatile and reliable fencing system. It is available in various specifications and is particularly well-suited to the road and rail, utilities, education, retail and industrial sectors.

Its imposing appearance makes for an effective visual deterrent, while spiked tops and cutting-resistant solid steel vertical pales ensure protection against unauthorised access and vandalism.

Palisade is the ideal solution for any business, school or public space in need of a strong, durable perimeter. Powder coating in an array of colours means that this product can be matched to corporate and brand identities or customised to assimilate with surrounding environments.

To ensure quality, specify your palisade fencing to be manufactured to British Standard.

Barkers hot dip galvanize our palisade products to protect the steel from the elements, rust and other deterioration, guaranteeing an exceptionally long lifespan.

Unlike several alternatives, Barkers palisade fencing systems cope with sloping ground up to 25 degree angles without cutting down bays or making modifications.

ARC Palisade

ARC palisade involves curving of the pale, adding to the intimidating appearance of standard palisade. For a modest increase in cost price, this innovation allows users to defend their properties with a superior deterrent and without the added installation costs of cranked posts and barbed or razor wire.

Key Features

- Palisade pales come in 'D' or 'W' profiles
- 'W' pale can be 2mm, 2.5mm or 3mm
- 'D' pale can be 2.5mm, 3mm and 4mm thick
- Pale tops can be single, triple point, round and notched or rounded only
- Available with welded, slotted or loose fishplates
- Manufactured to BS 1722, 12 and beyond
- Can be concreted-in/base plated for bolt down

Available with additional security features

- Curved Pales
- Barbed Wire
- Razor Wire
- Electrified Fence
- PIDs Systems
- Pales can be welded in place instead of using fixings
- Higher security CPNI, LPCB SR2 and SR3 options available



Specifications

Fence Height (m)	Pale Type W Thickness Available	Pale Type D Thickness Available	Post Centres (m)	Post Section (RHS)
1.2	2/2.5/3	3/3.5/4	2.75	100×55 IPE
1.5	2/2.5/3	3/3.5/4	2.75	100×55 IPE
1.8	2/2.5/3	3/3.5/4	2.75	100×55 IPE
2.0	2/2.5/3	3/3.5/4	2.75	100×55 IPE
2.1	2/2.5/3	3/3.5/4	2.75	100×55 IPE
2.4	2/2.5/3	3/3.5/4	2.75	100×55 IPE
3.0	2/2.5/3	3/3.5/4	2.75	100×55 IPE/127×76UB

Gate Dimensions

	Max Width (m)	Opening Inward	Opening Outward
Single Leaf	6.5m	180°	180°
Double Leaf	13m	180°	180°

Includes British Standard frame and posts, lockable drop bolt and slide latch, and a Locinox U-Safe