

**Product Code:**  
S450-65202-2844

**Stone Classification**  
Limestone

**Source**  
Portugal 

Date Created: 13/05/21



**Please note:**

Image shows sandblasted tonality variation and finish;  
Natural variations may occur between image and finished  
product.



**Project Shot:**

Moleanos Limestone paving.



Test	Value	BS EN
Apparent density (g/cm <sup>3</sup> )	2.66	1936: 2006
Water Absorption (%)	0.6	13755: 2008
Abrasion Resistance (mm)	18.5	14157: 2017
Flexural Strength (Mpa) LEV	11.9	12372: 2006
Flexural Strength (Mpa) Mean	13.6	12372: 2006
Compressive Strength (Mpa) Mean	139	1926: 2006
Slip Resistance Sandblasted Dry/Wet	76/68	14231: 2003
Freeze thaw: Before / After (Mpa)	13.9/11.9	12371: 2010
Open Porosity (%)	1.5	1936: 2006

**British Standards:**

Paving, Setts and Kerbs are  
CE marked to BS EN 1341,  
1342 and 1343.

**Tolerances:**

Stone dimensions are  
produced to meet class 1  
specification as a minimum.

**Quality Control:**

Stone supplied in  
accordance with ISO 9001  
quality standards.

**Maintenance:**

Clean warm water with natural soap would be the  
most common method of cleaning the stone.

We also offer a wide range specialist cleaning  
products and impregnators. Please contact out  
technical department for any further information.

*Inspiring beautiful  
landscapes*