







**5.7° FACE SEGMENTAL RETAINING WALL SYSTEM**

	BLOCK	CORNER BLOCK	CAP	DOUBLE-SIDED
				
<b>PROPERTIES</b>				
Length (mm)	440	440	215/185	440
Height (mm)	200	200	75	200
Depth (mm)	280	220	330	280
No. Per M <sup>2</sup> or Lm	11.2 blocks/m <sup>2</sup>	-	5 CAPS / lin m	11.2 blocks/m <sup>2</sup>
Appox. kg/ block	30	38.5	10	34
Face Angle	5.7°	5.7°	N/A	0°
Min. Inside Radius. (To back of block on bottom course) (m)	2.1	-	-	
Minimum Outside Radius (To back of block on top course) (m)	2.45	-	-	
<b>DELIVERY INFORMATION</b>				
Blocks per pack	45	32	120	32
<b>GENERAL PROPERTIES</b>				
Tolerances on all dimensions (mm)	±3			
Compressive Strength <sup>(1)</sup>	30N/mm <sup>2</sup> standard block			
Face Texture	Split face finish			
Aggregate	Stone			
Face Geometry	Stretcher			
BBA Approval	MacWall® to be used with BBA certified ParaGrid® W soil reinforcement geogrids. Agreement Certificate No. 16/H249,			


- (1) Compressive Strength determined by a 150mm cube from a block  
Colours made to order. Due to inaccuracies in the printing/reproduction process, the colours represented may vary from the final product. Please contact us for a sample.
- (2) Double sided block features a split face finish on both sides. It is used for vertical walls on top of the MacWall 5.7 structure. It can also be used for low impact resistant walls when detailed appropriately. Contact us for details.



Granite Grey



Limestone buff



Sandstone Red



Chromite Light Grey

**Maccaferri Ltd:**  
T: (+44) 1865 770555

[www.maccaferri.com/uk](http://www.maccaferri.com/uk)

**Rep of Ireland:**  
T: (+353) 18851662

[www.geostrong.net](http://www.geostrong.net)

**Specialist areas:**

Sales:  
Technical:  
Construction:

E: sales.uk@maccaferri.com  
E: technical.uk@maccaferri.com  
E: construction.uk@maccaferri.com

