



ENVIROMAT® NATURAL SEA COBBLES

■ **PRODUCT ORDER CODE** ENV-COBBLER

■ **STANDARD SIZE** 20kg bags
This product is sold per bag.

■ **DETAILS** Natural Sea Cobbles in sizes from 20mm to 40mm. Recommended for use on green roof installations as a fire break, to provide free draining areas or for habitat creation on biodiverse roofs. The naturally rounded stones are a blend of subtle greys and browns giving an aesthetically pleasing finish. In accordance with the GRO code, cobbles should be installed 300mm wide around all perimeters, including rooflights, rain outlets etc, and 500mm where there are building openings like doors, windows or opening roof lights. Cobbles should also be installed to a depth of 50mm or at least to the same depth as the substrate / plant layer. To ensure there is no substrate in the fire break it is advisable to use an edging product to provide separation.*

■ **USES** Fire break on living roof installations.
Creation of dry free-draining areas.
Habitat creation on biodiverse roofs.
Decorative landscaping for pathways etc.
Pond creation and rock pools.

**ROUNDED SEA PEBBLES
SUITABLE FOR A RANGE
OF LANDSCAPING
APPLICATIONS
INCLUDING GREEN
ROOFING.**

FEATURES

20-40mm (stone width).

Rounded.

Easy to handle.



Important - We cannot guarantee that all pebbles are rounded and smooth. As a naturally quarried product, sizes may vary.

*More information on the GRO code can be found at www.greenrooforganisation.org