



VITA RESIN

TECHNICAL DATA SHEET

VITA RESIN

TECHNICAL DATA SHEET



Vita Resin

Find out more or request a sample

Email sales@raftsystems.com or visit raftsystems.com

© 2025 Raft® Ltd. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. Any images and diagrams used in this sheet are intended only as illustrations. No rights can be derived from them.

Ref: **DS-AM-1223** Last update: August 2025

Vita resin gravel is RAAFT's premium decorative gravel surface.

Available in a range of colours and blends, the gravel surface is extremely hard wearing and provides visually stunning finishes. Vita resin is the ideal surface for driveways, pathways and walkways.

Vita resin is applied by mixing coloured aggregates with resin to form a level, permeable bound gravel system which is SuDs compliant.

Key specifications

- Permeable / SuDs compliant
- Durable and hard wearing
- Slip and weed resistant
- Suitable for heavy vehicles
- No loose stone

Recommended build up to create a permeable surface

- 16-24mm Vita resin*
- 50mm-80mm AC14 open textured binder course
- macadam (laid 7 days prior to gravel install)**
- Min 100-300mm MOT type 1 dependent on ground conditions
- Geotextile membrane
- Edge options: Concrete, Aluminium
- *Standard build up. Depths may vary depending on use / sub-base.
- ** Depth site dependent
- ***Dependent on sub-base. Terms and Conditions apply.




Find out more or request a sample


Email sales@raaftsystems.com or visit raaftsystems.com

VITA RESIN


TECHNICAL DATA SHEET



Autumn Quartz Angular Buff Desert Gold Amber Image Brittany Bronze



Black Granite Caramel Cocoa Danish Quartz Red Granite



Sterling Silver Granite Green



* Additional colours on request.

Base

The base must be dry and of sound construction

SURFACE DEPTH	CONCRETE	MACADAM	CONIPAVE	FLAGS	SOIL/GRASS	MOTTYPE 1
16mm Pedestrian	+	+	-	-	-	-
18mm Pedestrian	+	+	+	+*	-	-
18-20mm Pedestrian	+	+	-	-	-	-
24mm + -HGV/Tree Pits	+	+	-	-	-	+

*May require fibre glass mesh prior to application of gravel

Vita resin technical data

TECHNICAL DATA	VALUE
Material	Resin Bound Aggregate 7% min binder content
Curing Period	12 hours - Pedestrian Use 24-48 hours - Vehicle Use (weather dependent)

*May require fibre glass mesh prior to application of gravel

Find out more or request a sample

Email sales@raftsystems.com or visit raftsystems.com