



## DECLARATION OF PERFORMANCE

### Elevate PondGard™ EPDM CE

No. UKDoPPNDGv03L-2023-06-06

- 1. Unique identification code of the product-type:**  
Elevate PondGard™ EPDM CE
- 2. Identification of the construction product:**  
Part number prefix: W56PB or W56PG  
Lot number: see label  
Production date: see print on membrane
- 3. Intended use or uses:**  
Non reinforced, black, synthetic rubber membrane made of Ethylene-Propylene-Diene Terpolymer (EPDM) with a nominal thickness of 1,0 mm (MDV) used as a waterproofing membrane in decorative pond applications as covered by BS EN 13361 and BS EN 13362.
- 4. Name, registered trade name or registered trademark and contact address of the manufacturer:**  
  
Elevate PondGard™  
  

<i>Manufacturer:</i> Holcim Solutions and Products EMEA Ikaroslaan 75 1930 Zaventem Belgium	<i>Factory:</i> Holcim Solutions and Products US 1406 US Highway 371 Prescott, AR 71857 USA
---	---
- 5. Contact address of the authorised representative:**  
Not applicable
- 6. System or systems of assessment and verification of constancy of performance of the construction product:**  
System 2+
- 7. Construction product covered by the harmonized standards BS EN 13361 and BS EN 13362:**  
FM Approvals Limited, approved body No. 1725 has performed the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control under system 2+ and issued the certificate of conformity of the factory production control 1725-CPR-UKM0001.

**8. Declared performance:**

Essential characteristics		Performance			Designated technical specification
		Value 1.0 mm	Tolerance	Unit	
Tensile strength (MD/CD)	ISO R 527	9	-1	N/mm <sup>2</sup>	BS EN 13361:2004 BS EN 13361/A1:2006 BS EN 13362: 2005
Resistance to static puncture	BS EN ISO 12236	0.6	-0.1	kN	
Water permeability (Liquid tightness)	BS EN 14150	3.0 10 <sup>-6</sup>	± 10 <sup>-6</sup>	m <sup>3</sup> /m <sup>2</sup> d	
Durability – weathering (25 years)	BS EN 12224	Pass	-		
Durability – oxidation	BS EN 14575	Pass	-		
Durability – environmental stress cracking	ASTM D 5397-99	NPD	-		
Dangerous substances		None <sup>1)</sup>	-		

1) This product is an article as defined in article 3 of UK REACH regulation. It contains no components which are intended to be released under normal or reasonably foreseeable conditions of use. Based on current knowledge, this product does not contain substances of very high concern as listed in Annex XIV of the UK REACH regulation or in the “Candidate List of Substances of Very High Concern for Authorisation” published by HSE in concentrations above 0.1 % (w/w).

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Roshan Shrestha  
 Product Innovation and Technical Director  
 Holcim Solutions and Products EMEA  
 Zaventem, June 2023