

StronGuard SL2

Description

Barkers' StronGuard™ SL2 is the easiest LPS 1175 B3 (SR2) palisade fence to install on the market. It has been independently tested to withstand the rigorous testing of LPCB to LPS1175 B3 (previously known as SR2) to provide heavy-duty resistance and protection for over 3 minutes against experienced attack from tools of a higher mechanical advantage, such as, bolt cutters, claw hammers and drills.

This palisade security fence delivers the classic visual deterrent and ease of install as standard palisade, but goes a step further to considerably delay attacks to offer protection to various high security sites.

This system is the easiest of its kind to install with no specialist tooling or training is required. There is also no need to thread the pales through the rail, which avoids the potential for powder coating damage. StronGuard SL2 installs just like a standard palisade fence.

The high-security fence provides a valuable layer of protection for property from damage or theft. It also works to keep all staff and individuals that are on-site safe from intruders, who may otherwise be put at risk.

The StronGuard™ SL2 is flexible to its installation environment and unique ground conditions. Additionally, the fencing system can easily cope with up to 33 degrees of sloping without the need for onsite alterations.

This makes it an ideal palisade security fencing solution for locations at a higher risk of attack, or where more time to react is required.

Key Features

- Suited to remote and highly populated locations
- Combination of mesh and palisade
- No stepping aids
- Independently tested 358 mesh
- Material
- Welding
- Galv
- Powder coated in a range of RAL colours to

Additional Security Features

- T or Y post extensions to meet client specifications
- Razor wire
- PIDs systems
- Curved pales

Matching Entrance Security

- Manual swing vehicle gates
- Manual swing pedestrian gates
- Automatic or manual cantilever gates
- Automatic bi-folding swing gates
- Single 90° turnstile

Accreditations





Specifications

Fence Height (m)	Pale Types	Typical Pale Thickness (mm)	Post Centres (m)	Post Sections (UB)
2.0-3.0	W	2.5	2.75	127x76

Gate Dimensions

	Opening	Min Width (m)	Max Width (m)
Single Leaf	Inward	1m	2.5m
Double Leaf	Inward	2.5m	8.8m
Single Leaf	Outward	1m	2.6m
Double Leaf	Outward	2.6m	9m

Includes heavy duty hinges, lockable drop bolt and slide latch for an SR rated padlock, SR rated locks can be fitted

Material and Manufacturing Standards

- Material - Mild steel, hot dip galvanized
- All welded sections meet the BS 9606-1 standard
- Galvanized to British Standard EN ISO 1461 - 2009
- Powder coated in a range of RAL colours to BS 1722 Part 60