

ZAUN

Duo8 SR1 Q40

Manufacturer: Zaun Limited

Web: www.zaun.co.uk

Tel: +44 (0)1902 796699

Product reference:

Duo8 SR1.

Height:

[2.0 m].

[2.4 m].

Panel width:

[_____] - 3 m maximum.

Fixing:

[Bolt down].

[In ground].

[Wall].

Gates:

Pedestrian:

[Not required].

[Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements.

Vehicular:

[Not required].

[Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

Projection:

[Minimal].

[Standard].

Guidance for Duo8 SR1 from Zaun Limited

More about Duo8 SR1: As standard - Options

As standard

Finish:

Galvanized and polyester powder coated.

Mesh:

Duo8 SR1 mesh comprising 50 x 200 mm mesh with single 6 mm wires, vertical wires are at 50 mm centres, dual 8 mm horizontal wires at 200 mm centres.

Posts:

60 x 40 mm or 80 mm x 40 mm rectangular hollow section (RHS) spaced at a maximum of 3025 mm centres.

Post to panel fixing:

Panels fixed to posts with full height 40 x 5 mm clamp bar with stainless steel fixings at 400 mm centres. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar, with an enhanced over clip on the upper most and lower most fixings.

Gates:

ZAUN

Framed in a 50 x 50 mm RHS with Zaun Duo8 mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.

Options

Security rating:

SR1: Opportunist attack by bodily force using minimal tools (screwdriver, knife, pliers, etc.).