

## Duo8 Q40

**Manufacturer:** Zaun Limited

**Web:** [www.zaun.co.uk](http://www.zaun.co.uk)

**Tel:** +44 (0)1902 796699

### Product reference:

[Duo8 Clamp].

[Duo8 Zaunfix].

### Height:

[ \_\_\_\_\_ ] - 0.630–6.0 m, insert requirements.

### Fixing:

[Bolt down].

[In ground].

[Wall].

### Gates:

Pedestrian:

[Not required].

[Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements.

Vehicular:

[Not required].

[Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

### Safety capping:

[Not required].

[Required].

**Security rating:**

[Not required].

[SR1]. - Consult manufacturer for details.

**Projection:**

[Minimal].

[Standard].

**Guidance for Duo8 from Zaun Limited**

More about Duo8: As standard - Options

As standard

**Finish:**

Galvanized and polyester powder coated.

**Mesh:**

Duo8 mesh comprising 50 x 200 mm mesh with dual 8 mm horizontal wires at 200 mm centres and single 6 mm vertical wires at 50 mm centres.

**Posts:**

Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 2525 mm centres.

**Post to panel fixing:**

# ZAUN

## - Clamp:

Panels fixed to posts with full height 40 x 5 mm clamp bar with bolt fixings at 400 mm centres. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.

## - Zaunfix:

Panels fixed to posts with ZaunFix clip and bolt fixings at 400 mm centres.

## **Gates:**

Framed in a 50 x 50 mm RHS with Zaun Duo8 mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.

## **Options**

Security rating:

SR1: Opportunist attack by bodily force using minimal tools (screwdriver, knife, pliers, etc.).