



Super Rebound 6L Q40

Manufacturer: Zaun Limited

Web: www.zaun.co.uk

Tel: +44 (0)1902 796699

Product reference:

Super Rebound 6L.

Height:

[_____] - 1.2–3.68 m, insert requirements.

Gates:

Pedestrian:

[Not required].

[Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements.

Vehicular:

[Not required].

[Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

Guidance for Super Rebound 6L from Zaun Limited

More about Super Rebound 6L: As standard

As standard

Finish:

Galvanized and polyester powder coated.

ZAUN

Mesh:

Super Rebound 6 mesh comprising 50 x 66.6 mm mesh with single 5 mm vertical wires at 50 mm centres and dual 6 mm horizontal wires at 66.6 mm centres.

Posts:

Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 3025 mm centres.

Post to panel fixing:

Panels fixed to posts with full height 40 x 5 mm clamp bar with bolt fixings at 400 mm centres with EPDM inserts. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.

Gates:

Framed in a 50 x 50 mm RHS with Zaun Super 6 Rebound mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.