



Super Rebound 8L Q40

Manufacturer: Zaun Limited

Web: www.zaun.co.uk

Tel: +44 (0)1902 796699

Product reference:

Super Rebound 8L.

Height:

[_____] - 1.2–3.68 m, insert requirements.

Gates:

Pedestrian:

[Not required].

[Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements.

Vehicular:

[Not required].

[Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

Guidance for Super Rebound 8L from Zaun Limited

More about Super Rebound 8L: As standard

As standard

Finish:

Galvanized and polyester powder coated.

ZAUN

Mesh:

Super Rebound 6L mesh comprising 50 x 66.6 mm mesh with single 6 mm vertical wires at 50 mm centres and dual 8 mm horizontal wires at 66.6 mm centres.

Posts:

Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 3025 mm centres.

Post to panel fixing:

Panels fixed to posts with full height 40 x 5 mm clamp bar with bolt fixings at 200 mm centres with EPDM inserts. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.

Gates:

Framed in a 50 x 50 mm RHS with Zaun Super Rebound mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.