



William Bain Fencing Limited, T: +44 (0)1236 457333
 Lochrin Works, 7 Limekilns Road, F: +44 (0)1236 451166
 Blairlinn Industrial Estate, E: sales@lochrin-bain.co.uk
 Cumbernauld, UK G67 2RN www.lochrin-bain.co.uk

WILLIAM BAIN FENCING LTD
 EST 1859



LOCHRIN CLASSIC™

BEST VALUE WITH LIFETIME COST! A 'TRUE' PALISADE THAT CONFORMS TO BS1722 PART 12 - 2006.

Lochrin® Bain rivetless fixing system offers a security palisade fence with tamper free fixings, and pales that pass through the rails with no fixings required.

- Quick and simple installation.
- Adaptable using 3mm and 4mm thick pales for strength and reliable security.
- Heights of 0.90m to 3.6m.

APPLICATIONS:

- Boundary Security, Schools, Allotments, Industrial Units, Railways.
- Full specification drawings, Q40 tender documents and technical support available on request.

TECHNICAL INFORMATION

Post section: 102mm x 44mm RSJ section or 127mm x 76mm universal beams pending specification requirements.

2/3/4 no RSA Horizontal support rails.

- 45mm x 45mm x 6mm for 3mm pales.
- 50mm x 50mm x 6mm for 4mm pales.
- All with V shaped slots for pale insertion.
- 3mm or 4mm thick D section pales.

17 no Lochrin pales D Section type to a standard 2.75 metre panel.

2 pressed unique dimples.

2/3/4/ no Fishplate post and rail connectors.

2 no intermediate supports for bottom rail.

6/8/10 no M12 x 30mm cup square fixing bolts.

Heights – from 0.90m to 3.6m.

Hot Dipped Galvanised to BS EN ISO 1461 or Powder Coated to RAL Colours.

Raking panels: 450mm with 17 pales to a standard bay of 2.75 metre panel.

Security fencing to BS 1722 part 12.



GROUP OF COMPANIES

