

**TECHNICAL CHARACTERISTIC**

**Manufactured product technical features are validated by officially approved laboratory tests.**

• **Freeze resistance** 25 cycles of ice (-25°C) / defrosting (+15°C) without fissures, layers nor scaling having occurred.

• **Flexural and compressive strength** (UNE EN 1015-11 (196-1):

**Flexural:** 78 kgf/cm<sup>2</sup> (average value among the different standard colours)

**Compressive:** 440 Kp/cm<sup>2</sup> (average value among the different standard colours)

**Colours**

> Standard colours [without coloured pigments] grey [1] | white [2] | ochre [3]

> Other colours (with coloured pigments) on order. Percentage increase according to the colour characteristics and the order request.

**Finished**

Scoured.

Anti-graffiti superficial treatment optional.

Water repellents treatment superficial optional.

Manufactured in Architectural Cement

**ona**  
by Oriol Pardo

Elementos curvilíneos y sugerentes que, aunque están fabricados con un material de gran resistencia, suavizan los espacios.

Elements curvilinis i suggeridors que, tot i que estan fabricats en un material de gran resistència, suavitzen els espais.

Curvilinear, suggestive elements that soften spaces, in spite of being made from a very strong material.

Éléments curvilignes et suggestifs, mais fabriqués avec des matériaux à haute résistance, qui adoucissent les espaces.

Elementi curvilinei e suggestestivi, anche se fatti con materiale ad alta resistenza, che riescono ad ammorbidire gli spazi.

Kurvenförmige, attraktive Elemente, die, obwohl sie aus hochfestem Material hergestellt sind, eine entspannte Atmosphäre vermitteln.



**ona cóncavo** | 900 kg

**ona convexo** | 880 kg

